



PS-1200

Power Amp.

- Power Handling Per Channel @ 1kHz, 0.03% THD
- Maximum 6 Ch. Output: 1200W @ 8 Ohm
- Front Channel into 6 Ohms: 250W + 250W
- Center into 6 Ohms: 200W
- Rear into 6 Ohms: 150W + 150W
- Sub-Low into 6 Ohms / 30Hz - 180Hz: 400W
- Frequency Response: 20 - 20 kHz
- Voltage: 220-240V 50/60Hz
- Net Dimension 485(W) x 150(H) x 415 (D)mm
- Net Weight 30 Kgs.
- Mounting: Standards 19 inches rack mounting



PS-1600

Power Amp.

- Power Handling Per Channel @ 1kHz, 0.03% THD
- Maximum 6 Ch. Output: 1600W @ 8 Ohm
- Front Channel into 6 Ohms: 300W + 300W
- Center into 6 Ohms: 250W
- Rear into 6 Ohms: 200W + 200W
- Sub-Low into 6 Ohms / 30Hz - 180Hz: 600W
- Frequency Response: 20 - 20 kHz
- Voltage: 220-240V 50/60Hz
- Net Dimension 485(W) x 150(H) x 415(D)mm
- Net Weight 35 Kgs.
- Mounting: Standards 19 inches rack mounting